

HH492

High-Performance Wireless Scanner

Designed for business environment requiring a fast 1D /2D scanning solution with industrial grade durability, HH492 series delivers optimal scanning capabilities on traditional barcodes, digital screens, and damaged or difficult-to-read barcodes.

As Honeywell's new-generation 2D image wireless scanner, HH492 integrates GEN7 platform and 1472 module to decode all standard 1D/2D barcodes. The base allows for data transmission through the BLE module while also charging the device. These key features make the HH492 a valuable asset in inventory management in government departments, distribution centers express delivery outlets, retail, where fast barcode scanning and identification are required.

The Honeywell HH492 makes scanning easier and faster helping users quickly obtain data and minimizing input errors, which allows for increased productivity and simplified workflow.



The robust HH492 has excellent reading performance and can easily read poorly printed and damaged barcodes, which helps to reduce the risk of errors and improve operating efficiency.

FEATURES AND BENEFITS



Highly accurate and fast scanning of even damaged and poor-quality barcodes, with an extended scan distance to reach the bottom of the cart without bending and wasted time at point of sale.



Excellent flexibility and commonality for different customer requirements and various applications scenarios. Enhanced scanning performance, including product codes, digital codes, screen codes, government and hotel industry data matrixes and dot matrix codes.



A longer Bluetooth range compared to competitive devices enables greater operational flexibility for line busting or peak season satellite POS stations.



Equipped with USB data cable and a full accessories to meet different application scenarios and to facilitate the use.

HH492 Wireless Scanner Technical Specifications

MECHANICAL

Dimensions (L x W x H): 64 mm x 166 mm x 84 mm (2.5 in x 6.5 in x 3.3 in)

Charger/Communication Base: 130 mm x 86 mm x 85 mm (5.1 in x 3.4 in x 3.3 in)

Scanner Weight: 190 g (6.7 oz)

Charger/Communication Base: 150 g (5.29 oz)

ENVIRONMENTAL

Operating Temperature:

Scanner:

Charging: 5°C to 40°C (41°F to 104°F)

Non-Charging: -20°C to 50°C (-4°F to 122°F)

Communication Base:

Charging: 5°C to 40°C (41°F to 104°F)

Non-Charging: 0°C to 50°C (32°F to 122°F)

Storage Temperature:

Scanner/Communication Base: -40°C to 60°C (-40°F to 140°F)

Electrostatic Discharge (ESD) (Scanners and Cradles): ±8 kV indirect coupling plane, ±15 kV direct air

Humidity: 0% to 95% relative humidity, non-condensing

Anti-drop Performance

Scanner: Drop from 1.5m (4.9ft) to concrete floor for 5 times

Communication base: Drop from 1.0m (3.3 ft) to concrete floor twice

Environmental Sealing: IP40

Light Levels: 0 to 100,000 lux (9,290 foot-candles)

SYSTEM ARCHITECTURE

Operating Power (Charging): 2.5 W (500mA @ 5V USB input), 5W (1000mA @ 5V Adaptor input)

Standby Power: Charger/Communication Base: 0.25 W (50mA @ 5V)

Host System Interfaces: USB, HID

SCAN PERFORMANCE

Scan Pattern: Area Image (1040 x 720 pixel array) CMOS

Motion Tolerance: 25cm/s (9.8in/s) for 13 mil UPC at optimal focus

Scan Angle:

Horizontal: 39.2° nominal

Vertical: 27.4° nominal

Roll, Pitch, Skew: ±180°, ±65°, ±65

Barcode Types: Reads standard 1D, PDF, 2D, and DotCode symbologies

Note: Decode capabilities dependent on configuration.

WIRELESS

Radio/Range: 2.4 GHz to 2.5 GHz (ISM Band) Adaptive Frequency Hopping
Bluetooth v5.2 30 m (98 ft) line of sight with Honeywell charger/communication base

Power Options*:

Battery: 2730mAh Li-ion

Number of Scans: Up to 50,000 scans per charge

Expected Duration of Operation: 12 hours

Expected Charge Time: 4 hours

User Indicators: Good Decode LEDs, Rear View LEDs, Beeper (adjustable tone and volume), Charge Status Indicator

* Battery life depends on usage and other factors

WARRANTY

One- year factory warranty.

For a complete listing of all compliance approvals and certifications, please visit www.honeywell.com/PSScompliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywell.com/PSS-symbologies.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.

For more information

sps.honeywell.com

Honeywell Safety and Productivity Solutions

855 S Mint St
Charlotte, NC 28202
800-582-4263
www.honeywell.com